

DM 40

Ergonomic

Measuring principle

A Laser Distance Meter sends out a pulse of laser light to the target and detects the reflection. The meter then measures the time between those two events, and converts this to a distance.

Applications

This meter can be used to calculate distance, area, volume, and pythagorean distance in different units.

Features

- Pocket type.
- Clear display for better readability from all angles.
- Historical data review.
- Spirit bubble for checking level.

Technical Specifications

Model	Metrix+ DM 40
Measuring mode	Single and Continuous(max/min)
Measuring range	0.05 ~ 40m
Accuracy(Standard Deviation)	±2.0mm
Measuring units	Distance : m, ft, in Area : m², ft² Volume : m³, ft³
Laser Type	620 – 690nm, Class II, <1mW
Single Measurement time	0.25s
Other functionalities	Area, Volume, Pythagoras measurements Switchable measuring reference, Silence function, Battery power indication
Historical data review	20 groups of data
Auto switch off	Laser : 30s Instrument : 180s
Operating temperature	0 to 40°C
Storage Temperature	-20 to 65°C
Dimensions and weight	110mm×46mm×25mm; 72g(without batteries)
Batteries	2 x AAA 1.5V ; >5000 times working time(fully charged)
Standard Accessories	Laser distance meter, carrying case, batteries, technical manual.

Model and Specifications subject to change without notice.

Page 1 of 1 Rev 1902.01