

This is a wood moisture tester of DC resistance (probe type), with selection among 4 wood types and other type, which can be widely applied in the fields of testing the moisture content in the woods, bamboo ware, paper articles and those of wood fibre construction.

Features:

- Selection among 4 types of wood and other material
- Reading lock
- Review of maximum moisture reading
- Review of minimum moisture reading
- Battery volume alert
- Large non-parallax LCD with legible display
- Automatic/manual power off.



Wood type and other material :

Wood Type 1 : Rhodesia teak, Ormosia, Brazil walnut.

Wood Type 2 : Walnut, Clones wood, White poplar, Teak.

Wood Type 3: Fir, Douglas fir, Lauan, White ash, White fir, Maple, Ash wood, Cork wood, Sandalwood, Elm, Koombur, Hemlock, Borneol wood, Oak.

Wood Type 4 : Masson pine, Chile pine, Spruce, Larch, Apitong, Birch, Basswood

Other Material A : Karstenite.

Other Material A : Cement mortar.

Other Material A : Lime mortar.

Other Material A : Brick.

Technical Specifications :

Model	Metrix+ MM-2
Measuring range	Wood Type 1 : 0%-24%; Wood Type 2 : 0%-30% Wood Type 3 : 0%-37%; Wood Type 4 : 0%-41% Other Material A : 0%-6.8%; Other Material B : 0%-6.6% Other Material C : 0%-6%; Other Material D : 0%-12.2%
Precision	±2%
Resolution	0.10%
Operating temperature	0°C-40°C
Operating humidity	20%RH-90%RH
Automatic power off time	About 10 minute
Length of probe	9.8mm
Battery	2*1.5V AAA Battery
Size	135.6*55*29.4mm
Weight	107.7g() excluding battery
Packing	Blister Packing
Standard Accessories	Main unit, Manual